



APPROVALS®

Certificate of Conformity

Addendum

Certificate No.: SAA-193375-EA

Date of Issue: 3 December 2019

Class Description: Power Supply or Charger

Product Description: LED Driver (Independent, SELV, constant current)

Additional Models:

Trade Name: DIMMATE

Model No.	Rating
THU-06C0130-H	Input: 200-240V~ 50/60Hz 0.05A Output: 30-40Vdc 130mA 6W, Max 45Vdc
3A-THU-06C0130-H	Input: 200-240V~ 50/60Hz 0.05A Output: 30-40Vdc 130mA 6W, Max 45Vdc
HV5502D-6-130	Input: 200-240V~ 50/60Hz 0.05A Output: 30-40Vdc 130mA 6W, Max 45Vdc
TW-06C0130-H	Input: 200-240V~ 50/60Hz 0.05A Output: 30-40Vdc 130mA 6W, Max 45Vdc
CELL-06-FF-DRIVER	Input: 200-240V~ 50/60Hz 0.05A Output: 30-40Vdc 130mA 6W, Max 45Vdc
THU-06C0270-H	Input: 200-240V~ 50/60Hz 0.05A Output: 15-22Vdc 270mA 6W, Max 45Vdc
3A-THU-06C0270-H	Input: 200-240V~ 50/60Hz 0.05A Output: 15-22Vdc 270mA 6W, Max 45Vdc
HV5502D-6-270	Input: 200-240V~ 50/60Hz 0.05A Output: 15-22Vdc 270mA 6W, Max 45Vdc
TW-06C0270-H	Input: 200-240V~ 50/60Hz 0.05A Output: 15-22Vdc 270mA 6W, Max 45Vdc
THU-09C0210-H	Input: 200-240V~ 50/60Hz 0.05A Output: 30-40Vdc 210mA 9W, Max 45Vdc
3A-THU-09C0210-H	Input: 200-240V~ 50/60Hz 0.05A Output: 30-40Vdc 210mA 9W, Max 45Vdc
HV5502D-9-210	Input: 200-240V~ 50/60Hz 0.05A Output: 30-40Vdc 210mA 9W, Max 45Vdc
TW-09C0210-H	Input: 200-240V~ 50/60Hz 0.05A Output: 30-40Vdc 210mA 9W, Max 45Vdc

Model No.	Rating
CELL-09-FF-DRIVER	Input: 200-240V~ 50/60Hz 0.05A Output: 30-40Vdc 210mA 9W, Max 45Vdc
THU-10C0230-H	Input: 200-240V~ 50/60Hz 0.05A Output: 30-40Vdc 230mA 10W, Max 45Vdc
3A-THU-10C0230-H	Input: 200-240V~ 50/60Hz 0.05A Output: 30-40Vdc 230mA 10W, Max 45Vdc
HV5502D-10-230	Input: 200-240V~ 50/60Hz 0.05A Output: 30-40Vdc 230mA 10W, Max 45Vdc
TW-THU-10C0230-H	Input: 200-240V~ 50/60Hz 0.05A Output: 30-40Vdc 230mA 10W, Max 45Vdc
CELL-10-FF-DRIVER	Input: 200-240V~ 50/60Hz 0.05A Output: 30-40Vdc 230mA 10W, Max 45Vdc
THU-10C0270-H	Input: 200-240V~ 50/60Hz 0.05A Output: 28-35Vdc 270mA 10W, Max 45Vdc
3A-THU-10C0270-H	Input: 200-240V~ 50/60Hz 0.05A Output: 28-35Vdc 270mA 10W, Max 45Vdc
HV5502D-10-270	Input: 200-240V~ 50/60Hz 0.05A Output: 28-35Vdc 270mA 10W, Max 45Vdc
TW-THU-10C0270-H	Input: 200-240V~ 50/60Hz 0.05A Output: 28-35Vdc 270mA 10W, Max 45Vdc
3A-THU-10C0330-H	Input: 200-240V~ 50/60Hz 0.05A Output: 18-25Vdc 330mA 10W, Max 45Vdc
HV5502D-10-330	Input: 200-240V~ 50/60Hz 0.05A Output: 18-25Vdc 330mA 10W, Max 45Vdc
TW-10C0330-H	Input: 200-240V~ 50/60Hz 0.05A Output: 18-25Vdc 330mA 10W, Max 45Vdc


For and on Behalf of
SAA Approvals Pty Ltd

SAA Approvals Pty Ltd as accredited by JAS-ANZ under ISO/IEC 17065 and declared a RECS under Qld Electrical Safety Act 2002 and Electrical Safety Regulations 2013 certifies in accordance with the SAA Approvals Electrical Product Safety Certification Scheme that the product nominated in this certificate complies with standard/s listed.

When using the RCM the requirements of all relevant parts of AS/NZS 4417 applicable to the article must be fulfilled.

For SAA Contact Details and to verify this Certificate go to:
www.saaapprovals.com.au

JAS-ANZ



www.jas-anz.org/register



Issued: 03-12-19 193375/2